



NOTE: All relevant materials are complied with RoHS directive .

1823-3		
P1		P2
1	—————	1
2	—————	2
3	—————	3
4	—————	4
5	—————	5
6	—————	6
7	—————	7
8	—————	8
9	—————	9
SHIELD	—————	SHIELD

No.	DESCRIPTION	Q'TY	Supplier
5	BLACK HEAT SHRINK TUBE ϕ 3.0*18mm	2	M743
	ALUMINUM FOIL 25*60mm	2	M579
	MOLDED PE COLOR TRANSPARENT		M280
	MOLDED PVC GREY		M304
4	UL2464 9C 28AWG, ALUM-MYLAR FOIL SHIELDING WITH DRAIN WIRE, OD 5.0mm, JACKET GREY, DRAWING No. EMAL2809C-052	L-20mm	M304
3	MOLDED THUMBSCREW #4-40, LENGTH 40mm, GREY	4	M95
2	DB9 FEMALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	1	M108
1	DB9 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	1	M108

APPROVED		D9/9MF-xx	Cable Length Unless Other Spec. Tolerances: 0 ~200mm \pm 10mm 201~1000mm \pm 20mm 1001 ~1500mm \pm 25mm 1501~2100mm \pm 30mm 2100mm \uparrow \pm 40mm
CHECKED	HU		
DRAWING	NIE		
DATE	29/NOV/10	ITEM NO.	1823-3
		UNF:mm	

CHECKED