



MARKING:

LSZH

|         |          |
|---------|----------|
| 1003-17 |          |
| P1      | P2       |
| 1       | 1 BROWN  |
| 2       | 2 RED    |
| 3       | 3 ORANGE |
| 4       | 4 YELLOW |
| 5       | 5 GREEN  |
| 6       | 6 BLUE   |
| 7       | 7 PURPLE |
| 8       | 8 GREY   |
| 9       | 9 BLACK  |
| SHIELD  | SHIELD   |

★ NOTE: All relevant materials are complied with RoHS directive .

| No. | DESCRIPTION  |             | Q'TY | Supplier |
|-----|--|-------------|------|----------|
| 4   | BLACK PVC TUBE $\phi$ 3.0*22mm   | A4HA26-0743 | 2    | M304     |
|     | COPPER FOIL 33*65mm  | A6LA11-0309 | 2    | M309     |
|     | MOLDED PE COLOR TRANSPARENT  | A5BA02-0280 |      | M280     |
|     | MOLDED PVC BLACK,LSZH  |             |      |          |
| 3   | NON-UL 9C 26AWG, ALUM-MYLAR FOIL AND COPPER BRAD SHIELDING WITH DRAIN WIRE, OD 6.0mm, LSZH, JACKET BLACK, DRAWING No. EMAB2609C-1265 |             | Lmm  | M304     |
| 2   | MOLDED THUMBSCREW #4-40, LENGTH 46.5mm, BACK,LSZH  | A6AA30-0095 | 4    | M95      |
| 1   | DB9 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR   | A1AA17-0108 | 2    | M108     |

|          |            |  |
|----------|------------|--|
| APPROVED | 2012.11.19 | Cable Length Unless Other Spec.<br>Tolerances:<br>0 ~200mm ±10mm<br>201~1000mm ±20mm<br>1001 ~1500mm ±25mm<br>1501~2100mm ±30mm<br>2100mm↑ ±40mm |
| CHECKED  | 李淑萍        |  |
| DRAWING  | PENG       |  |

CHECKED