



9461-47			
P1		P2	
1	—	1	RED 24#
2	—	2	WHITE
3	—	3	GREEN
4	—	4	BLACK 24#
SHIELD	—	SHIELD+BRAID	

* NOTE: All relevant materials are complied with RoHS directive .

5	MOLDED PVC GRAY-WHITE(MZB7070)	H1BK01-0304G25		M304
4	MOLDED PVC GRAY-WHITE(MZB7070)	H1BK01-0304G25		M304
3	USB 2.0 CABLE, UL STYLE 1 TWISTED PAIR 28AWG AND 2C 24AWG, AMA BRAID 64% SHIELDING WITH DRAIN WIRE,OD 4.5mm,JACKET GRAY-WHITE(MZB7070),DRAWING No.EUAB2801P2402C-139	H5KH29-0304G25	480mm	M304
2	USB B MALE 2.0, GOLD FLASH ON CONTACTS, WHITE INSULATOR, SHORT A PIERCE TYPE	A1HB15-0454	1set	M454
1	USB A MALE 2.0, GOLD FLASH ON CONTACTS, WHITE INSULATOR, SHORT A PIERCE TYPE	A1HA22-0454	1set	M454
No.	DESCRIPTION		Q'TY	Supplier

APPROVED				Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm
CHECKED	HU			
DRAWING	XJW			

DATE	25/NOV/14	ITEM NO.	CU500G-x	UNIT:mm	
------	-----------	----------	----------	---------	--

CHECKED