



9509-17			
P1		P2	
1	—————	1	RED 24#
2	⌢⌢⌢	2	WHITE
3	⌢⌢⌢	3	GREEN
4	—————	4	BLACK 24#
SHIELD	—————	SHIELD	

\* NOTE:All relevant materials are complied with RoHS directive.

3	MOLDED PVC BLACK	H1BF01-0304B01		M304
2	USB 2.0 CABLE, UL STYLE 1 TWISTED PAIR 28AWG AND 2C 24AWG, AMA BRAD, OD 4.5mm, JACKET BLACK, DRAWING No.EUAG2B01P2402C-139	H5KH29-0304B01	2000mm	M304
1	USB A MALE 20, GOLD FLASH ON CONTACTS, WHITE INSULATOR, SHORT A PERCE TYPE	A1HA49-0108	2set	M108
No.	DESCRIPTION	Q'TY		Supplier

APPROVED		Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm† ±40mm
CHECKED	HU	
DRAWING	PENG	

DATE	25/APR/12	ITEM NO.	CU520B-2	UNIT:mm	
------	-----------	----------	----------	---------	--

CHECKED