



NOTE: All relevant materials are complied with RoHS directive .

5	MOLDED PVC BLACK	H1BF01-0304K09		M304
4	MOLDED PVC BLACK	H1BF01-0304K09		M304
3	USB 2.0 CABLE, UL STYLE 1 TWISD PAIR 28AWG AND 2C 24AWG,OD 4.5mm, AMA BRAID, JACKET BLACK, DRAWING No. EUAB2801P2402C-139	H5KH29-0304K09	L-20mm	M304
2	MINI USB 5P MALE 2.0, GOLD FLASH ON CONTACTS, BLACK INSULATOR	A1HE09-0471	1SET	M471
1	USB A MALE, GOLD FLASH ON CONTACTS, WHITE INSULATOR, CRIMP TWO PIECES TYPE	A1HA22-0454	1SET	M454
No.	DESCRIPTION		Q'TY	Supplier

APPROVED	木子 2015.12.23	CU550B-xxx	Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm		
CHECKED	陳瑞雯				
DRAWING	JIANG				
DATE	23/DEC/15	ITEM NO.	9525-36	UNIT:mm	

