


USB A/M Micro USB 5PIN Male



Nr. / No.	Länge / Length (m)
CU551B-015	0.15
CU551B-030	0.30
CU551B-060	0.60
CU551B-1	1.00
CU551B-1.8	1.80
CU551B-3	3.00
CU551B-5	5.00

Micro-USB Daten- und Ladekabel

- Verbinder: USB-A Stecker > Micro USB-B St.
- Innenleiter: AWG22/28
- Material: Kabelmantel: PVC
Innenleiter: BC, CCS
Isolierung: PVC, HDPE
Kontakte: vernickelt
Geflecht: AL
- Schirmung: doppelt
- USB Standard: High Speed USB 2.0
- Datenrate: max. 480 Mbit/s
- RoHS-konform

Micro USB data and charging cable

- USB-A male > Micro USB-B female
- Inner conductor: AWG22/28
- Material: Sheath: PVC
Conductors: BC, CCS
Insulation: PVC, HDPE
Contacts: nickel-plated
Braid: AL
- Shielding: double
- USB Standard: High Speed USB 2.0
- Data rate: max. 480 Mbps
- RoHS compliant

Änderungen

Datum	Name	gez.:	Datum	Name
25.02.2019	tf	gez.:	30.07.2014	tf
		gepr.:	30.07.2014	tf
		Norm:		
Änderungen vorbehalten / Subject to change				

Bezeichnung	Blatt
USB MICRO-B SCHWARZ	
Zeichnungs-Nr.:	von