

P1: M-Y745A		Customer No:	
M-745A			
P3: M-438A			
P4: M-SR959A			
P5: M-746A			
P6: M-355A			

MINI DSP 20M

⑧ ① ⑤ ④ ⑦ ③ ⑥ ② ⑨

2 7 19 1 6 14 20

18 16 4 3 5 9 11

9K00

P1	P2
3	3 RED
5	5 WHITE
1	1 SHIELD
9	9 BROWN
11	11 WHITE
7	7 SHIELD
16	16 BLACK
18	18 WHITE
14	14 SHIELD
8	
2	2 RED
4	4 GREEN
6	6 BLUE
19	19 PURPLE
13	
20	20 WHITE
SHIELD	SHIELD

⚠

NOTE: All relevant materials are complied with RoHS directive.

9	PE HOOD COLOR TRANSPARENT		1	M304
8	PE HOOD COLOR TRANSPARENT		1	M304
7	MOLDED PVC APPLE WHITE	H1BF01-0304W20		M304
6	UL1061 28AWG INSULATOR WIRE, LENGTH 50mm, DRAWING NO.EH002801C-024	H5SE07-0304	1	M304
	BLACK HEAT SHRINK TUBE $\varnothing 2.5*10\text{mm}$	A4HA39-0959	3	M959
	BLACK HEAT SHRINK TUBE $\varnothing 0.8*10\text{mm}$	A4HA08-0959	3	M959
	HD15M PLASTIC HOOD APPLE WHITE		1SET	M854
5	UL1061 28AWG INSULATOR WIRE, LENGTH 20mm, DRAWING NO.EH002801C-024	H5SE07-0304	2	M304
	BLACK HEAT SHRINK TUBE $\varnothing 0.8*4\text{mm}$	A4HA08-0959	1	M959
	MOLDED PE COLOR TRANSPARENT	A5BA02-0280		M280
	MOLDED PVC APPLE WHITE	H1BF01-0304W20		M304
4	UL20276 [(32AWG*1Pair+AL+D+MY)*3Pcs+(32AWG*5C)]+AL+D+65%AMA BRAID OD 5.0mm, JACKET APPLE WHITE, DRAWING No.EAAB3203P3205C-578		3010mm	M304
3	MOLDED THUMBSCREW #4-40, LENGTH 56.25mm, APPLE WHITE		2	M95
2	HD15 MALE, GOLD FLASH ON CONTACTS & GOLD CONNECTOR, BLUE INSULATOR, WITH PCB		1	M916
1	MINI DP20 MALE, GOLD FLASH ON CONTACTS & GOLD CONNECTOR, WHITE INSULATOR, WITH PCB		1	M977
No.	DESCRIPTION		Q'TY	Supplier
APPROVED		Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm		
CHECKED	HU			
DRAWING	JIANG			
DATE	28/SEP/12	ITEM NO.	9K00	UNIT:mm

RE.1 2012.09.28

MODIFY PLUG AND PIN SPEC

CHECKED