



MARKING :
 550MHz (UL) E305668 TYPE CM 24AWG 75°C CSA 204790 CM 75°C
 ETL VERIFIED TIA/EIA-568-C.2 UTP CAT.6 RoHS COMPLIANCE BATCH NO.

8233	
P1	P2
1	1 WHITE/ORANGE
2	2 ORANGE
3	3 WHITE/GREEN
6	6 GREEN
4	4 BLUE
5	5 WHITE/BLUE
7	7 WHITE/BROWN
8	8 BROWN

NOTE: All relevant materials are complied with RoHS directive .

3	MOLDED PVC GREY-WHITE	H1BP01-0304G07		M304
2	4 TWISTED PAIRS CAT.6 24AWG UTP, OD 6.2mm, JACKET GREY-WHITE DRAWING No. EU002404P-221	H5AJ01-0304G07	L+15mm	M304
1	8P8C MODULAR PLUG (P8-S80-6), GOLD PLATING 50u" ON CONTACTS, SHORT TYPE, TRIPLEX	A1NA38-0209	2	M209
No.	DESCRIPTION	Q'TY Supplier		
APPROVED		PCUTP6GR-X Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm		
CHECKED	HU			
DESIGNER	JIANG			
DRAWING	ZHU			
DATE	27/MAY/21	ITEM NO.	8233	UNIT:mm

CHECKED

