



MA 001B (DB9F/25M ADAPTOR)

PIN OUT: 09Female 25Male

1	-----	8
2	-----	3
3	-----	2
4	-----	20
5	-----	7
6	-----	6
7	-----	4
8	-----	5
9	-----	22
G	-----	G

Label: orange color with white character

One side: SERIAL PORT ADAPTORS D9/D25

The other side: MINI ADAPTER

**SPECIFICATION**

INSULATOR: PBT Glass fibre reinforced UL 94 VO

CONTACT: Brass

CONTACT PLATING: Gold plated over nickel

SHELL: Tin plated shell

CURRENT RATING: 3 AMP

DIELECTRIC STRENGTH: 500V AC for one minute

INSULATOR RESISTANCE: 500MΩ min at 500V DC

TEMPERATURE: -25°C—+105°C

NOTE: All relevant materials are complied with RoHS directive

				Edition	A01			
				SCALE	2:1			
				UNIT	mm			
				Page	1/1			
Customer	REVISION	DESCRIPTION	DATE	PART NO.		DRG NO.	DATE	
	1	修改規格(R.O.C. PATENT 105471 改為 MINI ADAPTER)	2001/12/8	SA9/25FM		TM0052-02	8/Dec-2001	
				DRAWN		CHECKED	APPRD	