



MA 001C (DB9M/25M ADAPTOR)

PIN OUT: 09Male

25Male

1	-----	8
2	-----	3
3	-----	2
4	-----	20
5	-----	7
6	-----	6
7	-----	4
8	-----	5
9	-----	22
G	-----	G

Label: orange color with white character

One side: SERIAL PORT ADAPTORS D9/D25

The other side: MINI ADAPTER

SPECIFICATION

INSULATOR: PBT Glass fibre reinforced UL 94 V0

CONTACT: Brass

CONTACT PLATING: Gold plated over nickel

SHELL: Tin plated shell (Nickel Silver)

CURRENT RATING: 3 AMP

DIELECTRIC STRENGTH: 500V AC for one minute

INSULATOR RESISTANCE: 500MΩ min at 500V DC

TEMPERATURE: -25°C—+105°C

NOTE: All relevant materials are complied with RoHS directive .

				Edition	A01			
				SCALE	2:1			
				UNIT	mm			
	1	修改貼紙(R.O.C. PATENT 105471 改爲 MINI ADAPTER)	2001/12/8	Page	1/1			
Customer	REVISION	DESCRIPTION	DATE		UNLESS OTHERWISE SPECIFIED TOLERANCE: 0.0: ±0.20 0.00: ±0.15 0.000: ±0.05	PART NO. 31D1-26100	DWG NO. TM0053-02	DATE 8/Dec-2001
					DRAWN	CHECKED	APPRD	